## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

## Supplier's name or trade mark: Solus

Supplier's address: Help Desk, Knockmitten Lane 1, D12AX7F Dublin 12 Dublin, IE

Model identifier: 060057

## Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS		
Light source cap-type	E14				
(or other electric interface)					
Mains or non-mains:	MLS	Connected light source (CLS):	No		
Colour-tuneable light source:	No	Envelope:	-		
High luminance light source:	No				
Anti-glare shield:	No	Dimmable:	No		
Product parameters					

		Product para	ineters			
Parameter		Value	Parameter	Value		
General product parameters:						
Energy consum mode (kWh/100 up to the nearest	0 h), rounded	7	Energy efficiency class	E		
Useful luminous indicating if it re in a sphere (36 cone (120 <sup>o</sup> ) or in (90 <sup>o</sup> )	fers to the flux 0°), in a wide	806 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700		
On-mode po expressed in W	ower (P <sub>on</sub> ),	6,5	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,00		
Networked stand for CLS, express rounded to the s	sed in W and	-	Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set	80		
Outer	Height	35	Spectral power	See image		
	Width	35	distribution in the	in last page		
without	Depth	103	-			
I	-	I	1	Page 1		

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load				
Claim of equivalent power <sup>(a)</sup>	Yes	If yes, equivalent power (W)	60			
		Chromaticity coordinates (x and y)	0,382 0,380			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	0	Survival factor	0,90			
the lumen maintenance factor	0,96					
Parameters for LED and OLED mains light sources:						
displacement factor (cos φ1)	0,50	Colour consistency in McAdam ellipses	6			
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	If yes then replacement claim (W)	-			
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,4			

(a)'-' : not applicable;

(b)'\_-' : not applicable;

